

TDS Packer Disposable GX-Midi (CX), 0-65 Bar, 1/2" pipe connection

Part no: 80008XX XX = Drill hole size 38-45mm

To be used together with Manual mounting injection pipes 1/2" or Mechanical mounting injection pipes 1/2"



Dimensions

Drill hole Ø mm*	Part no	Outside Ø packer mm	Sealing aperture mm	Tightening Torque (Nm)	Max injection pressure**	Weight (kg)
38	8000838	36,5	37-40	90-120	65	0,48
41	8000841	39	40-44	90-120	65	0,50
45	8000845	43	44-47	90-120	65	0,56

* Note: Additional packer sizes/diameters available on request.

** Max injection pressure is reported for compressed packer detached from injection pipe, supported by lock washer only (3 lock washers).

Maximum injection pressure varies with diameter according to table above.

If injection pipe is attached to the packer, and the injection pipe is thoroughly anchored, a substantial higher injection pressure can be used.

Material specification

Central pipe:	25x3mm EN 10305-3 max. pressure 160 Bar
Washers:	EN 101.49-2 S315 MC, 240 YP
Check valve:	SS 1914-01
Rubber:	NR/SBR (Packer) NR (None-return valve)
Locking washers:	SS1770, DIN1.1231, CK67

Packer sketch with general measurements

